

Gouging Carbon electrodes 碳棒

Round Copper-Coated Carbon electrodes(D.C) 圆形镀铜碳棒(直流)

Model	Dia*Length		Current Ranger(A)	Regular Apply
	mm	inches		
B503.2	3.2*305	1/8*12'	130-180	For gouging, cutting and boning
B504	4*305(355)	5/32*12' (14')	150-200	
B505	5*305(355)	3/16*12' (14')	200-250	
B506	6*305(355)	15/64*12' (14')	300-350	
B506.5	6.5*305(510)	1/4*12' (14')	320-370	
B507	7*305	9/32*14'	350-400	
B508	8*305(355)(510)	5/16*12' (14')(20')	40 -450	
B509	9*305(355)	23/64*12' (14')	450-500	
B510	10*305(355)(510)	3/8*12' (14')(20')	500-550	
B511	11*305(355)(510)	7/16*12' (14')(20')	600-650	
B512	12*305(355)	15/32*12' (14')	750-850	
B513	13*305(355)(430)(510)	1/2*12' (14')(17')(20')	800-1000	
B516	16*305(430)(510)	5/8*(14')(17')(20')	1000-1200	
B519	19*305(430)(510)	3/4*(14')(17')(20')	1200-1600	

Jointed Copper-Coated Carbon electrodes(D.C) 连接镀铜碳棒(直流)

Model	Dia*Length		Current Ranger(A)	Regular Apply
	mm	inches		
B508J	8*355	5/16*14'	500-550	Ldeal for eityer automatic or manual torch applications. Continuous electrode feed excellent quality and eliminates stub loss
B509J	9*355	23/64*14'	550-600	
B510J	10*355(430)	3/8*14' (17')	600-650	
B511J	11*355(430)	7/16*14' (17')	650-700	
B512J	12*355(430)	15/32*14' (17')	700-800	
B513J	13*430(510)	1/2*17' (20')	800-1000	
B516J	16*430(510)	5/8*17' (20')	1000-1200	
B519J	19*430(510)	3/4*17' (20')	1200-1600	

